



KINEMATICA POST-PROCESSING

Kinematica is a GNSS/INS post processed kinematic (PPK) software.

It processes raw GNSS and INS data to achieve a higher level of accuracy than real time INS.

Kinematica is compatiable with all of Advanced Navigation's INS solutions.

PERFORMANCE

SPATIAL



0.04° Roll and Pitch



0.08 ° Heading

SPATIAL FOG DUAL



0.005 ° Roll and Pitch



0.007 ° Heading

KEY FEATURES

- Dual Antenna Heading Support
- Forward and Reverse Processing
- Precise Orbits and Clocks
- Odometer Aiding Support


APPLICATIONS













MAXIMUM INS ACCURACY

Kinematica processes data backward and forward in time with advanced algorithms.

This allows it to significantly reduce errors and extract the very best performance possible from an inertial navigation system.



KINEMATIC GNSS POSITIONING

Kinematica features kinematic GNSS post processing which provides a 200x increase in position accuracy over standard GNSS.

Kinematica automatically downloads the closest RINEX base station data and outputs position to an accuracy of 8 mm.



PRECISE POINT POSITIONING (PPP)

The Precise point positioning (PPP) algorithm models GNSS errors to provide decimetre-level positioning accuracy.

PPP can be used anywhere in the world, for example at sea or in remote areas, where real-time kinematic (RTK) accuracy in unavailable.



FORWARD & REVERSE PROCESSING

Kinematica's PPK algorithm parses data forwards and backwards to fill satellite outages and ignore errors that would normally affect a real time solution.

Data is processed in both diurections multiple times in order to obtain the highest accuracy results.



DUAL ANTENNA HEADING

For dual antenna systems, Kinematica supports tightly coupled dual antenna heading processing which significantly increases heading accuracy.



SPECIFICATIONS

SPATIAL ACCURACY

| 0.9 m |
|-----------|
| 1.2 m |
| 0.02 m |
| 0.03 m |
| 0.18 m |
| 0.22 m |
| 0.005 m/s |
| 0.04° |
| 0.08° |
| |

SPATIAL DUAL ACCURACY

| Horizontal Position Accuracy (no base station) | 0.9 m |
|---|-----------|
| Vertical Position Accuracy (no base station) | 1.2 m |
| Horizontal Position Accuracy (with base station) | 0.008 m |
| Vertical Position Accuracy (with base station) | 0.015 m |
| Horizontal Position Accuracy(60s after outage) | 0.16 m |
| Vertical Position Accuracy (60s after outage) | 0.19 m |
| Velocity Accuracy | 0.005 m/s |
| Roll & Pitch Accuracy | 0.03° |
| Heading Accuracy | 0.06° |

SPATIAL FOG ACCURACY

| Horizontal Position Accuracy(no base station) | 0.7 m |
|--|-----------|
| Vertical Position Accuracy(no base station) | 1.1 m |
| Horizontal Position Accuracy (with base station) | 0.008 m |
| Vertical Position Accuracy(with base station) | 0.015 m |
| Horizontal Position Accuracy(60s after outage) | 0.13 m |
| Vertical Position Accuracy(60s after outage) | 0.14 m |
| Velocity Accuracy | 0.005 m/s |
| Roll & Pitch Accuracy | 0.005° |
| Heading Accuracy | 0.01° |

SPATIAL FOG DUAL ACCURACY

| 0.7 m |
|-----------|
| _ 1.1 m |
| 0.008 m |
| 0.015 m |
| 0.10 m |
| 0.11 m |
| 0.005 m/s |
| 0.005° |
| 0.007° |
| |

TECHNICAL FEATURES

| Supported Navigation Systems | GPS L1, L2, L5 GLONASS L1, L2 Galileo E1, E5 BeiDou B1, B2 |
|--------------------------------|---|
| GNSS/INS Log File Format | ANPP |
| Base Station Log File Format | RINEX v2.*RINEX v3.* |
| Configuration | Fully Automatic |
| Kinematic Processing | Yes |
| Dual Antenna Heading Support | Yes |
| Odometer Aiding Support | Yes |
| Precise Orbits and Clocks | Yes |
| Forward and Reverse Processing | Yes |
| Zero Velocity Updates | Yes |
| | |



HEAD OFFICE

+61 2 9099 3800

sales@advancednavigation.com

Level 12, 255 George Street Sydney NSW 2000 Australia

NORTH AMERICA

+1 863 777 0224

usasales@advancednavigation.com

1420 Kettner Blvd, Suite #100 San Diego CA 92101 United States

EUROPE

+44 20 3875 3118

uksales@advancednavigation.com

One Kingdom Street, Paddington Central London, W2 6BD United Kingdom

SUBSEA RESEARCH CENTRE

+61 8 6146 5600

245 Balcatta Road, Balcatta 6021 WA Australia

